










**DEVICE AND METHOD FOR MAINTAINING AND GUIDING A RISER, AND
METHOD FOR TRANSFERRING A RISER ONTO A FLOATING SUPPORT**

Patent number: WO0111184
Publication date: 2001-02-15
Inventor: HALLOT RAYMOND (FR); BAYLOT MICHEL (FR);
 ROCHER XAVIER (FR)
Applicant: BOUYGUES OFFSHORE (FR); HALLOT RAYMOND
 (FR); BAYLOT MICHEL (FR); ROCHER XAVIER (FR)
Classification:
 - international: **E21B17/01; E21B19/00; E21B43/01; E21B17/00;
 E21B19/00; E21B43/00; (IPC1-7): E21B19/00;
 E21B17/01; E21B43/01**
 - european: E21B17/01; E21B19/00A; E21B43/01F
Application number: WO2000FR02244 20000803
Priority number(s): FR19990010417 19990809

Also published as:

 EP1204807 (A1)
 US6672804 (B1)
 FR2797464 (A1)
 EP1204807 (B1)


Cited documents:

 US4617998
 US4913238
 WO9007049
 GB2188899
 GB2302555
 more >>

Report a data error here

Abstract of WO0111184

The invention concerns a device for maintaining and guiding a floating riser (1) relative to a floating support (2) comprising articulation means (3) integral with said floating support enabling: (a) said riser to rotate about a horizontal axis (XX', YY') perpendicular to the longitudinal axis (ZZ') of said riser; and (b) said riser to slide along the longitudinal axis (ZZ') and said riser to be guided laterally in a horizontal plane (XX', YY') perpendicular to said longitudinal axis of the riser, and the articulation means (3) comprise: friction pads (5), said pads being mounted on a pad support (7) enabling said pads (5) to pivot, said pads (5) preferably co-operating with rollers (9) such that said rollers (9) are supported on said riser, and enabling it to slide, and said riser is only supported on said pads (5), when said rollers (9) move under the effects of the lateral movements of said riser.



Data supplied from the esp@cenet database - Worldwide